

Feel the precise printer solution from the



Improver	nent of Print Speed
Enhanced FINE [™] I	maging Technology
300, 600 & 1200dpi	Printing Resolution
	New Input Hopper
Remova	ble Output Hopper
Support o	f Transparent Cards
Sup	port of CR79 Cards
Front-	Side Mag Encoding
All-in-On	e type Lock System
the second se	

Endeavor for Perfection

IDP's new SOLID-510 is the next generation of its mid-range ID Card Printer platform. The SOLDI-510 inherits the most successful and proven elements of the SOLID-500 series -IDP's longest running ID Card Printer. Enhancements to the SOLID-510 include careful selection of highly reliable parts, the application of a new state-of-the art CPU and application specific features for unique projects.

The new SOLID-510 offers an upgrade path from single side printing (510S), to dual side printing (510D), and to dual side printing with lamination (510L). The SOLID-510L also uses IDP's patented Direct Lamination which is the industry's first adoption of direct lamination technology to drastically reduce heat-up time, save energy, and optimize the application of laminate to the card.

Performance - Essence of Card Printer

The core spirit of a card printer is its print quality, print speed and stability. IDP's new SOLID-510 card printer increases print speeds up to by 10%, enhances print quality by optimizing precise ribbon movement, and provides faster processing speed by utilizing a new powerful CPU.

Careful Consideration of User Convenience

From the initial design of the SOLID-510 Series, IDP has taken careful consideration of the end-user to create an easy to use and flexible card printer. The SOLID-510 offers a larger card loading capacity (up to 200 cards), a choice of output direction, new cartridge loading lamination, support of transparent magnetic cards, optional support of CR79 card and an optional all-in-one type lock system are all features of the new SOLID-510.

With a more advanced SOLID-510 from IDP, card issuance will be easier and more productive than ever before.



SOLID Applications ensure proper card issuance and data management with SOLID series printers at no extra cost.

- Design and Print (Images, Photos, Texts, etc.)
 1D & 2D Barcode printing
- Auto portrait
- (Auto face detection & adjustment of size & position) - Card design templates
- Plug-in for supporting external devices
- Convenient issuance of cards and data management
 Magnetic stripe (MS), contact & contactless smart card encoding by using plug-in program



SOLID series provides effective security features for access control and data encryption.

SOLID series has a password verification function to provide administrator and user authentications.

SOLID series can set a specific authorized PC for encoding and printing cards.

SOLID series can encrypt data transmitted on USB and can support SSL (Secure Socket Layer) protocol on ethernet communications.



SOLID series can utilize the network printer server for encoding and printing cards.

SOLID Ethernet module can not only print cards but also encode MS, contact and contactless smart card through the network.

SOLID Ethernet module has OCP(Open Card Print) protocol which can encode and print cards by using commands on multiple platforms without installing the printer driver

Available encoding the contact & contactless smart card by Ethernet.

Single sided ID CARD PRINTER **SOLID-510S**

SPECIFICATIONS

PRINTING		SYSTEM	
 Print Type 	Dye-Sublimation	 Memory 	64MB RAM
 Print Area 	Edge to Edge	 Display & Button 	2 Line LCD / 2 LED Buttons
 Resolution 	300dpi (Color & Mono), 600 & 1200dpi (Mono only)	 Supported Platforms 	Microsoft Windows 7/ 8/ 10, Mac OS, Linux
 Dual Sided Printing 	Option (with Flipper)	 Communication 	USB, Ethernet (Option)
CARD		Power	Free Voltage (AC100/ 240V, 50~60Hz) / 48W
Card Feeding Card Size	Automatic ISO CR80 or ISO CR79 (Option-Factory installed)	Temperature/HumiditySecurity	15~35℃ / 35~70% Physical Lock & Kensington Lock (Option)
 Card Thickness 	0.38mm (15mil), 1.0mm (40mil)	DIMENSIONS / WEIGH	Т
 Card Type 	PVC, PET, Composite PVC	 Millimeter (WxLxH) 	165 x 390 x 210
PRINT SPEED		 Inch (WxLxH) 	6.5 x 15.4 x 8.3
Monochrome	5 sec_/card (720 cards/hour)	 Kg/lbs 	4.5 / 10
YMCKO	Front-in & Front-out : Max, 17 sec /card (212 cards/hour)	ENCODING OPTIONS	
	Front-in & Back-out : Max, 16 sec /card (225 cards/hour)	MagneticContact	ISO7811 (Track I, II, III Read/ Write, HiCo/ LoCo), JIS I
CAPACITY			ISO 7816 (ID-1)
Input HopperOutput Hopper	100 cards / 200 cards with cover open Front : 40 cards / Back : 100 cards (Optional Back-side Stacker)	Contactless CERTIFICATIONS	MIFARE, ISO 14443 (Type A/ B), ISO 15693, DESFIRE, iCLASS
ouputroppor		CB (€ F© @ 🕅	

FEATURES



*Print Speed : May change under specific condition.

CONSUMABLES

YMCKO	250 Cards/Roll	Full Color Ribbon wit Resin Black & Overla
ҮМСКОК	200 Cards/Roll	Full Color Ribbon wit Resin Black, Overlay & Black for Back Sid
YMCFKO	200 Cards/Roll	Full Color Ribbon wit UV Panel, Resin Blac and Overlay
НҮМСКО	350 Cards/Roll	Half Panel Size Color Ribbon with Resin Blac and Overlay

SECONIT FILIVIS		
HPF	250 Cards/Roll	Hologram Patch Film
CPF	250 Cards/Roll	Clear Patch Film

MONO RIBBONS		
КО	600 Cards/Roll	Black with Overlay
К	1200 Cards/Roll	Black
W	1200 Cards/Roll	White
В	1200 Cards/Roll	Blue
R	1200 Cards/Roll	Red
MG	1200 Cards/Roll	Metallic Gold
MS	1200 Cards/Roll	Metallic Sliver
SO	1200 Cards/Roll	Scratch-Off



Specifications and availability may change without notice.

3370 N. San Fernando Rd., Ste. 202, Los Angeles, CA 90065

> 1-888-383-6083 www.multicard.com info@multicard.com

©2017 IDP Corporation. All rights reserved.

SMART, SOLID, Wise, SMART BIT are trademarks or registered trademarks of IDP Corporation. Specifications and availability may change without notice